

## Loader Ticket Windsor

Loader Ticket Windsor - Gehl articulated loaders have been made to suit almost any situation. They offer great traction and optimal maneuverability thanks to a heavy-duty oscillating joint which offers 45-degree turning angles left and right, together with 10 degrees of oscillating in both directions. Access is granted to confined and tight places by narrow engine widths. Nearly all skid-steer loaders with similar operating capacities are unable to compete. The bucket and tires on the Gehl machine follow a stable turn radius also. This means the back tires of the loader follow the course of the front tires.

Fantastic hydraulic performance, along with several time-saving features on the Gehl articulated loaders, offers customers with the hydraulic power and precision they have come to expect from all of the Gehl equipment. Bucket float and lift arm features permit these equipment to execute light scraping and rearward leveling actions. Flat-face couplers, with the two easily reachable auxiliary hydraulic lines power many tools and make changing the accessories a simple task to complete.

Gehl articulated loaders have distinctively designed lift arms which are made to achieve maximum strength, fast cycle times and great visibility. The specialized linkage design allows for mechanical self-leveling action in both the upward and downward directions. It can also simply execute exceptional bucket dump angles at the mid and top ranges of the lift path along with offering excellent forward reach. Models 340 and 140 have parallel kind linkage and the model 540 has "Z" bar type linkage. These linkage layouts provide great bucket breakout forces from two thousand four hundred thirty three pounds on the model 140 to ten thousand seven hundred forty nine pounds on the model 540.

Gehl articulated loaders are popular world-wide for their unsurpassed visibility, ease of operation and supreme ergonomics. The 540 and 340 models have a total cab enclosure option obtainable. This offers better comfort and safety for the individual operating it. Safe operation and 360 degree visibility is maintained by placing the one operating it above the load to ensure an excellent view of the accessory. An inching pedal permits the operator to vary ground speed while maintaining a fixed engine speed. This particular feature allows the person operating it to optimally run attachments while making sure precise engine speed control. A multi-function joystick controls the differential lock and auxiliary hydraulic functions, bucket, travel direction, float as well as the lift arm.